

Certification

[HOME \(HTTPS://WWW.CSAGROUP.ORG/\)](https://www.csagroup.org/) / [TESTING AND CERTIFICATION \(HTTPS://WWW.CSAGROUP.ORG/TESTING-CERTIFICATION/\)](https://www.csagroup.org/testing-and-certification/) / [CSA GROUP PRODUCT LISTING \(HTTPS://WWW.CSAGROUP.ORG/TESTING-CERTIFICATION/PRODUCT-LISTING/\)](https://www.csagroup.org/testing-certification/product-listing/) / CERTIFICATION RECORD | CSA GROUP.

Certification Record | CSA Group.

Contact an Expert
(<https://www.csagroup.org/contact/>).

[Back to Product List \(/testing-certification/product-listing/\)](/testing-certification/product-listing/)

CUSTOMER	CLASS	FILE NUMBER
Southwire Company One Southwire Dr Carrollton Georgia United States 30119	5831-01 (/testing-certification/product-listing/class/?class=5831-01) WIRES - Flexible Cord	090458_0_000

To the requirements of standard CSA C22.2 No. 49-18 Flexible Cords and Cables:

SJ, SJO, SJOO rated 60/75/90/105C (-20C), 300V, FT2; optional: FT1, VW-1. Multi-conductor round construction. Number of conductors: 2 to 6. Size range: 18-10 AWG. Insulation: EPDM. Jacket: CPE or CR.

SJOW, SJOWW rated 60/75/90/105C (-40C), 300V, FT2; optional: -50C, FT1, VW-1. Multi-conductor round construction. Number of conductors: 2 to 6. Size range: 18-10 AWG. Insulation: EPDM. Jacket: CPE or CR.

S, SO, SOO rated 60/75/90/105C (-20C), 600V, FT2; optional: FT1, VW-1. Multi-conductor round construction. Number of conductors: 2 or more. Size range: 18-2 AWG. Insulation: EPDM. Jacket: CPE or CR.

SOW, SOOW rated 60/75/90/105C (-40C), 600V, FT2; optional: -50C, FT1, VW-1. Multi-conductor round construction. Number of conductors: 2 or more. Size range: 18-2 AWG. Insulation: EPDM. Jacket: CPE or CR.

SJE, SJEO, SJEOO rated 90/105C dry (-20C), 300V, FT2; optional: FT1. Multi-conductor round construction. Number of conductors: 2 to 6. Size range (AWG or kcmil): 18-10. Insulation: TPE. Jacket: TPE.

SJEW, SJEOW, SJEOWW rated 90/105C dry (-40C), 300V, FT2; optional: -50C, -60C, -70C, FT1. Multi-conductor round construction. Number of conductors: 2 to 6. Size range (AWG or kcmil): 18-10. Insulation: TPE. Jacket: TPE.

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJ, SJT rated 600 dry (-20C), 300V, FT2. Multi-conductor round construction. Number of conductors: 2 to 6. Size range (AWG or kcmil): 18-10. Insulation: PVC. Metallic shield: optional. Jacket: PVC.

SJTW, SJTOW rated 60C dry (-40C), 300V, FT2. Multi-conductor round construction. Number of conductors: 2 to 6. Size range (AWG or kcmil): 18-10. Insulation: PVC. Metallic shield: optional. Jacket: PVC.

ST, STO rated 60C dry (-20C), 600V, FT2. Multi-conductor round construction. Number of conductors: 2 or more. Size range (AWG or kcmil): 18-2. Insulation: PVC. Metallic shield: optional. Jacket: PVC.

STW, STOW rated 60C dry (-40C), 600V, FT2. Multi-conductor round construction. Number of conductors: 2 or more. Size range (AWG or kcmil): 18-2. Insulation: PVC. Metallic shield: optional. Jacket: PVC.

SPT-1 rated 60/75/90/105C dry (-20C), 300V, FT2; optional: FT1, VW-1. Multi-conductor flat-parallel construction. Number of conductors: 2 or 3. Size range (AWG or kcmil): 20-18. Insulation: PVC.

SPT-2 rated 60/75/90/105C dry (-20C), 300V, FT2; optional: FT1, VW-1. Multi-conductor flat-parallel construction. Number of conductors: 2 or 3. Size range (AWG or kcmil): 18-16. Insulation: PVC.

SPT-3 rated 60/75/90/105C dry (-20C), 300V, FT2; optional: FT1, VW-1. Multi-conductor flat-parallel construction. Number of conductors: 2 or 3. Size range (AWG or kcmil): 18-10. Insulation: PVC.

NISPT-1 rated 60/75/90/105C dry (-20C), 300V, FT2; optional: FT1. Multi-conductor flat-parallel construction. Number of conductors: 2 or 3. Size range (AWG or kcmil): 20-18. Insulation: PVC. Jacket: PVC.

NISPT-2 rated 60/75/90/105C dry (-20C), 300V, FT2; optional: FT1. Multi-conductor flat-parallel construction. Number of conductors: 2 or 3. Size range (AWG or kcmil): 18-16. Insulation: PVC. Jacket: PVC.

To the requirements of standard CSA C22.2 No. 49-14 Flexible Cords and Cables:

Type	Rated Voltage (Volt)	Size of Conductors (AWG)*	No of Conductors	Insul Type	Jacket Type	Notes
------	----------------------	---------------------------	------------------	------------	-------------	-------

- Temperature rating 60C:

TPT	300	-	2	PVC	-	1,2
PXT	125	20	2	PVC	-	1,2
S	600	18-2	2 or more	NR/IR	NR/IR	1,2,8
SJ	300	18-10	2-6	NR/IR	NR/IR	1,2,8
SO	600	18-2	2 or more	NR/IR	CR,NBR/PVC	1,2,4,8,9
SJO	300	18-10	2-6	NR/IR	CR,NBR/PVC	1,2,4,8,9
ST, STO, STOO	600	18-2	2 or more	PVC	PVC	1,2,5,8,9

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJTW, SJTOW	300	18-10	2-6	PVC	PVC	1,2,8,9,12,13
SJTOOW	300	18-10	2-6	PVC	PVC	1,2,8,9
STW, STOW	600	18-2	2 or more	PVC	PVC	1,2,8,9,12
STOOW	600	18-2	2 or more	PVC	PVC	1,2,8,9
CXWT	300	18-16	2	PVC	-	1,2
DRT	300	10-4	4	PVC	PVC	1,2
PXWT	300	18,16	2	PVC	-	1,2
SJOOW	300	18-10	2 or more	NR/IR	NBR/PVC, CR,CPE	2,4,8,9,12
SOW	600	18-2	2 or more	NR/IR	NBR/PVC, CR,CPE	2,4,8,9
TPT	300	-	2	PVC	-	1,2
PXT	125	20	2	PVC	-	1,2
S	600	18-2	2 or more	NR/IR	NR/IR	1,2,8
SJ	300	18-10	2-6	NR/IR	NR/IR	1,2,8
SO	600	18-2	2 or more	NR/IR	CR,NBR/PVC	1,2,4,8,9
SJO	300	18-10	2-6	NR/IR	CR,NBR/PVC	1,2,4,8,9
ST, STO, STOO	600	18-2	2 or more	PVC	PVC	1,2,5,8,9
SJT, SJTO, SJTOO	300	18-10	2-6	PVC	PVC	1,2,5,8,9
SVT, SVTO, SVTOO	300	18,17,16	2,3	PVC	PVC	1,2,5,8,9
TX	125	20	2	PVC	-	1,2
SJTW, SJTOW	300	18-10	2 or more	PVC	PVC	1,2,8,9,12,13
SJTOOW	300	18-10	2 or more	PVC	PVC	1,2,8,9

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

PXWT	300	18,16	2	PVC	-	1,2
SJOOW	300	18-10	2 or more	NR/IR	NBR/PVC, CR,CPE	2,4,8,9,12
SOW	600	18-2	2 or more	NR/IR	NBR/PVC, CR,CPE	2,4,8,9

• Temperature rating 90C:

SJOW, SJOOW	300	18-10	2-6	EPR	CR,CPE	2,4,8,9
SOW, SOOW	600	18-2	2 or more	EPR	CR,CPE	2,4,8,9
SO	600	18-2	2 or more	EPR	CR	2,4,8,9
SJO	300	18-10	2-6	EPR	CR	2,4,8,9
HPN	300	18,16,14	2,3	CR	-	2,7,10
HPN	300	16,18	2,3	CSM	-	2,7,10
HPN	300	18-12	2,3	CPE	-	1,2,10
HSJO	300	18-12	2, 3 or 4	EPR	CR	2,4,8,9
HOISTWAY	600	18	2-4	PVC	PVC	1,2
DRT	300	10-4	4	PVC	PVC	1,2
SJOW, SJOOW	300	18-10	2 or more	EPR	CR,CPE	2,4,8,9
SOW, SOOW	600	18-2	2 or more	EPR	CR,CPE	2,4,8,9
SO	600	18-2	2 or more	EPR	CR	2,4,8,9
SJO	300	18-10	2-6	EPR	CR	2,4,8,9
HPN	300	18,16,14	2,3	CR	-	2,7,10
HPN	300	16,18	2,3	CSM	-	2,7,10
HPN	300	18-12	2,3	CPE	-	1,2,10
HSJO	300	18-12	2, 3 or 4	EPR	CR	2,4,8,9

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJT, SJTO, SJT00	300	18-10	2-6	PVC,TPE	PVC,TPE	1,2,5,6,8,9
SVT, SVTO, SVTOO	300	18,17,16	2,3	PVC,TPE	PVC,TPE	1,2,5,6,8,9
SJTW, SJTOW, SJTOOW	300	18-10	2-6	PVC	PVC	1,2,8,9,11,12,13
STW, STOW, STOOW	600	18-2	2 or more	PVC	PVC	1,2,8,9,11,12
SJTW, SJTOW, SJTOOW	300	18-10	2-6	TPE	TPE	1,2,8,9,12,15
STW, STOW, STOOW	600	18-2	2 or more	TPE	TPE	1,2,8,9,12,15
HPN	300	18-12	2,3	CPE	-	1,2,10
ST, STO, STOO	600	18-2	2 or more	PVC	PVC	1,2,6
SJT, SJTO, SJT00	300	18-10	2-6	PVC,TPE	PVC,TPE	1,2,5,6,8,9
SVT, SVTO, SVTOO	300	18,17,16	2,3	PVC,TPE	PVC,TPE	1,2,5,6,8,9
SJTW, SJTOW, SJTOOW	300	18-10	2 or more	PVC	PVC	1,2,8,9,11,12,13
STW, STOW, STOOW	600	18-2	2 or more	PVC	PVC	1,2,8,9,11,12
SJTW, SJTOW	300	18-10	2 or more	TPE	TPE	1,2,8,9,12
STW, STOW	600	18-2	2 or more	TPE	TPE	1,2,8,9,12

* mm² conductors sizes also apply.

Notes:

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

[Accept all cookies](#)

- .7. Types having a single '0' or double '00' in the type designation are recognized as '0' or resistant, e.g. SJTO, S00W etc.
- .8. Insulation type for bonding (grounding) conductor, XLPE.
- .9. Investigated for 1000 hours Xenon Arc and Water Spray Test.
- .10. May be marked -50C.
- .11. Type SJTW, -40C may include a breather tube having a minimum thickness of not less than 0.40mm.
- .12. In all colours including clear and translucent.
- .13. Types SJTOOW(TPE) and STOOW(TPE) may be marked -60°C.
- .14. Non-integral construction.

• Max temperature rating 60°C:

Type	Max Volt	Size of Conductors (AWG)	No of Conductors	Insulation Type	Jacket Type	Notes
SVT	300	18-16	2 or 3	PVC	-	5,12,13
SVTO	300	18-16	2 or 3	PVC	-	5,12,13
SJTW	300	18-10	2 to 6	PVC	PVC	10,11,12,13
SJTOW	300	18-10	2 to 6	PVC	PVC	10,11,12,13
STW	600	18-2	2 or more	PVC	PVC	10,11,12,13
STOW	600	18-2	2 or more	PVC	PVC	10,11,12,13
SVT	300	18, 17, 16	2, 3	PVC	-	8,12
SJT	300	18-10	2 to 6	PVC	PVC	2,5,7,12, 13
SJTO	300	18-10	2 to 6	PVC	PVC	5,7,12,13
ST	600	18-2	2 or more	PVC	PVC	2,5,7,12,13
STO	600	18-2	2 or more	PVC	PVC	5,7,12,13
PXT	125	20	2	PVC	-	5,12,13
DRT	300	10-4	4	PVC	PVC	12,13
SJ	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
S	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
S	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16

- Max temperature rating 90°C:

Type	Max Volt	Size of Conductors (AWG)	No of Conductors	Insulation Type	Jacket Type	Notes
SJ	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
S	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16

- Max temperature rating 105°C:

Type	Max Volt	Size of Conductors (AWG)	No of Conductors	Insulation Type	Jacket Type	Notes
SVT	300	18-16	2, 3	PVC	PVC	7, 12, 13
SVTO	300	18-16	2, 3	PVC	PVC	7, 12, 13
ST	600	18-2	2 or more	TPE	TPE	5, 12, 13
STO	600	18-2	2 or more	TPE	TPE	5, 12, 13
STOO	600	18-2	2 or more	TPE	TPE	5, 12, 13
STW	600	18-2	2 or more	TPE	TPE	5, 9, 12, 13
STOW	600	18-2	2 or more	TPE	TPE	5, 9, 12, 13

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJTOW	300	18-10	2 to 6	TPE	TPE	5, 9, 12, 13
SJTOOW	300	18-10	2 to 6	TPE	TPE	5, 9, 12, 13
SJTOOW	300	18-10	2 to 6	PVC	PVC	12, 13
SJTOW	300	18-10	2 to 6	PVC	PVC	12, 13
SJTW	300	18-10	2 to 6	PVC	PVC	12, 13
STOOW	600	18-2	2 or more	PVC	PVC	12, 13
STOW	600	18-2	2 or more	PVC	PVC	12, 13
STW	600	18-2	2 or more	PVC	PVC	12, 13
ST	600	18-2	2 or more	PVC	PVC	7, 12, 13
STO	600	18-2	2 or more	PVC	PVC	7, 12, 13
SJT	300	18-10	2-6	PVC	PVC	5, 7, 12, 13
SJTO	300	18-10	2 to 6	PVC	PVC	5, 7, 12, 13
STW	600	18-2	2 or more	TPE	TPE	12, 13, 15
STOW	600	18-2	2 or more	TPE	TPE	12, 13, 15
STOOW	600	18-2	2 or more	TPE	TPE	12, 13, 15
SJTW	300	18-2	2 to 6	TPE	TPE	12, 13, 15
SJTOW	300	18-2	2 to 6	TPE	TPE	12, 13, 15
SJTOOW	300	18-2	2 to 6	TPE	TPE	12, 13, 15
SJ	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOO	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
SJOOW	300	18-10	2 to 6	EPDM	CPE	5, 10, 12, 13, 16
S	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOO	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SOOW	600	18-2	2 or more	EPDM	CPE	5, 10, 12, 13, 16
SJTW	300	18-10	2 to 6	TPE	TPE	9, 12, 13
SJTOW	300	18-10	2 to 6	TPE	TPE	9, 12, 13
SJTOOW	300	18-10	2 to 6	TPE	TPE	9, 12, 13

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

1. Deleted.
2. Types SJT and ST may be shielded.
3. Deleted.
4. Deleted.
5. Flame classification - FT1.
6. Deleted.
7. May have an aramid fiber strength member centered in the conductor copper strands for wire sizes 18 or 16 AWG. See report for details.
8. Type SVT rated 60°C may be marked FT1, FT2 or FT4.
9. Low temperature rating: -50°C.
0. Optional shielding.
 1. Low temperature rating: -40°C.
 2. In all colours except for clear and transparent.
 3. Flame classification - FT2.
 4. Insulation type for bonding (grounding) conductor, PVC, PE, TPE, XLPE.
 5. Low temperature rating: -70°C.
 6. Flame classification - FT4.

Type	Max Volt	Size of Conductors (AWG)	No of Conductors	Insul. Type	Jacket Type	Notes
------	----------	--------------------------	------------------	-------------	-------------	-------

- Max temperature rating 60C:

SVT, SVTO, SVTOO	300	18,17,16	2,3	PVC	PVC	2,5,9,11,14
------------------	-----	----------	-----	-----	-----	-------------

SJT, SJTO, SJTOO	300	18-10	2-6	PVC	PVC	2,5,9,11,12,14
------------------	-----	-------	-----	-----	-----	----------------

ST, STO, STOO	600	18-2	2 or more	PVC	PVC	2,5,9,11,12,14
---------------	-----	------	-----------	-----	-----	----------------

SJOO	300	18-10	2-6	EPR, CSM, CPE	CR, CPE, CSM, NBR/PVC	2,5,8,11,12,14
------	-----	-------	-----	---------------	-----------------------	----------------

SJOW, SJOOW	300	18-10	2-6	EPR, CSM	CR, CPE	2,5,8,11,12,14
-------------	-----	-------	-----	----------	---------	----------------

SOO, SO, S	600	18-2	2 or more	EPR, CSM, CPE	CR, CPE, CSM, NBR/PVC	2,5,8,11,12,14
------------	-----	------	-----------	---------------	-----------------------	----------------

SOW, SOOW	600	18-2	2 or more	EPR, CSM	NBR/PVC, CR	2,5,8,11,12,14
-----------	-----	------	-----------	----------	-------------	----------------

SJTW, SJTOW, SJTOOW	300	18-10	2-6	PVC	PVC	2,5,9,11,12,14
---------------------	-----	-------	-----	-----	-----	----------------

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

SJTOOW						
ST, STO, STOO, STW, STOW, STOOW	600	18-2	2 or more	LDPE	PVC	2,5,17
CXWT	300	18,16	2	PVC	-	2,4,14
CXWT	600	14-12	2	PVC	-	2,4,14
DRT	300	10-4	4	PVC	PVC	2,4, 9,14
TX	125	20	2	PVC	-	2,13,14
PXWT	300	18,16	2	PVC	-	2,4,14
PXT	125	20	2	PVC	-	2,13,14
SV, SVO	300	18,16	2,3	EPR	CR, NBR/PVC, CSM,CPE	2,5,8,11,12,14
SJ,SJO	300	18-10	2-6	EPR, CSM, CPE	CR, NBR/PVC, CSM, CPE	2,5,8,11,12,14
Hoistway Cable	300 600	20 to 12 18 to 12	2-4 (PAR) 2-75 (Twisted)	PVC	PVC (optional)	5, 14

- Max temperature rating 90C:

HPN	300	18,16,14	2,3	CSM	-	1,2,3,14
HPN	300	18,16,14	2,3	CR	-	2,3,4,14
HPN	300	18,16,14	2,3	CPE	-	2,3,4,14
SJOO, SJO	300	18-10	2-6	EPR, CSM, CPE	CR, CPE, CSM, NBR/PVC	2,5,8,11,12,14
SJOW, SJOOW	300	18-10	2-6	EPR, CSM	CR, CPE	2,5,8,11,12,14
SOO, SO	600	18-2	2 or more	EPR, CSM, CPE	CR, CPE, CSM, NBR/PVC	2,5,8,11,12,14
SOOW, SOW	600	18-2	2 or more	EPR CSM	CR, CPE, CSM NBR/PVC	2,5,8,11,12,14
HSJO	300	18-12	2,3,4	CR, EPR	CR, NBR/PVC, CSM, CPE	2,5,8,14

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

Accept all cookies

DRT	300	10-4	4	PVC	PVC	2, 5, 14, 15
-----	-----	------	---	-----	-----	--------------

- Max temperature rating 105C:

SVT, SVTO, SVTOO	300	18,17,16	2,3	PVC	PVC	2,5,9,11,12,14
SJT, SJTO, SJTOO	300	18-10	2-6	PVC	PVC	2,5,9,11,12,14
ST, STO, STOO	600	18-2	2 or more	PVC	PVC	2,5,9,11,12,14
HPN	300	18,16,14	2,3	CSM	-	1,2,3,11,14
SJTOO, SJT, SJTO	300	18-10	2-6	TPE	TPE	2,5,9,11,12,14
SJTOW, SJTOOW, SJTW	300	18-10	2-6	TPE	TPE	2,5,9,11,12,14
ST, STO, STOO	600	18-2	2 or more	TPE	TPE	2,5,9,11,12,14
STOW, STOOW, STW	600	18-2	2 or more	TPE	TPE	2,5,9,11,12,14
SO, SOO	600	18-2	2 or more	EPR, CSM	CSM, CPE	2,5,8,11,12,14
SOW, SOOW	600	18-2	2 or more	EPR	CSM, CPE	2,5,8,11,12,14
SJO, SJOO	300	18-10	2-6	CSM, EPR	CPE, CSM	2,5,8,11,12,14
SJOW, SJOOW	300	18-10	2-6	EPR	CPE	2,5,8,11,12,14
SJTW, SJTOW, SJTOOW	300	18-10	2-6	PVC	PVC	2,5,9,11,12,14
STW, STOW, STOOW	600	18-2	2 or more	PVC	PVC	2,5,9,11,12,14

Notes:

1. In dark colours only.
2. Flame test, FT2.
3. Insulation type for bonding (grounding) conductor, XLPE.
4. In light and dark colours.
5. In all colours except clear and transparent.
6. Insulation type for bonding conductor (grounding), PE.
7. Insulation type for bonding conductor (grounding), PVC.

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. [Learn More \(https://www.csagroup.org/legal/privacy-policy/#cookies\)](https://www.csagroup.org/legal/privacy-policy/#cookies)

[More information](#)

[Accept all cookies](#)

... reserved for future use
... 7. Low Leakage.

Contact an
Expert

We're always here to help. Let's talk.

We're here to answer your questions and help you get started right away. Call or send us a message anytime.

[Contact Us \(/contact\)](#)

Contact an Expert
(https://www.csagroup.org/contact)



<https://www.csagroup.org>

[FAQs \(/faq/\)](#)

[CSA OnDemand™](#)

http://store.csagroup.org/ondemand/report?language=en_US

[Informs & Notices \(/informs-notices/\)](#)

[Submit an Incident Report \(/submit-a-report\)](#)

[Agreement on Acceptance of Components \(/agreement-acceptance-components/\)](#)

<http://community.csagroup.org/login.jspx?referer=%252Findex.jspa>

[Product Alerts & Recalls](#)

[\(/product-alerts-recalls/\)](#)

[Report Suspect Counterfeit Marks](#)

[\(/testing-certification/marks-labels/brand-protection/reporting-suspect-counterfeit-marks\)](#)

[Resources & Insights \(/resources-insights/\)](#)

[Standards Research \(/standards/standards-research/\)](#)

[CSA Group Product Listing \(/testing-certification/product-listing/\)](#)

Sign up for our
Newsletter

<https://www.csagroup.org/n>

<http://www.facebook.com/CSAGroup>

<http://www.linkedin.com/company/csagroup>

<http://www.youtube.com/user/CSAGroup>

<http://www.instagram.com/csagroup>

<http://www.tiktok.com/csagroup>

Cookies on CSA Group

We use Cookies to create a secure and effective website experience for our customers. For more information about Cookies and how you can disable Cookies, visit our privacy policy page. **Learn More** (<https://www.csagroup.org/legal/privacy-policy/#cookies>)

[More information](#)

Accept all cookies