

UL Online Certifications Directory

QLIW.E194613 Receptacles, Pin-and-Sleeve Type

Page Bottom

Receptacles, Pin-and-Sleeve Type

[See General Information for Receptacles, Pin-and-Sleeve Type](#)

INTERPOWER CORP
100 INTERPOWER AVE
PO BOX 115
OSKALOOSA, IA 52577 USA

E194613

| Receptacle | Rating | Code |
|------------|-----------------|---------------|
| 8425210X | 30A, 125VAC | a, b, f, g, h |
| 8425220X | 30A, 120/208VAC | a, b, f, g, h |
| 8425230X | 30A, 250VAC | a, b, f, g, h |
| 8424210X | 30A, 125VAC | a, f, g, h |
| 8424220X | 30A, 250VAC | a, f, g, h |
| 8424230X | 30A, 250VAC | a, f, g, h |
| 8423110X | 20A, 125VAC | a, b, f, g, h |
| 8423120X | 20A, 250VAC | a, b, f, g, h |
| 8423210X | 30A, 125VAC | a, b, f, g, h |
| 8423220X | 30A, 250VAC | a, b, f, g, h |
| 8423230X | 30A, 250VAC | a, b, f, g, h |
| 8425216X | 30A, 125VAC | a, b, f, g, h |
| 8425226X | 30A, 120/208VAC | a, b, f, g, h |
| 8425236X | 30A, 250VAC | a, b, f, g, h |
| 8425316X | 60A, 125VAC | a, b, f, g, h |
| 8423153X | 20A, 480VAC | a, b, f, g, h |
| 8423253X | 30A, 480VAC | a, b, f, g, h |
| 8423113X | 20A, 125VAC | a, b, f, g, h |
| 8423123X | 20A, 250VAC | a, f, g, h |
| 8423213X | 30A, 125VAC | a, f, g, h |
| 8423223X | 30A, 250VAC | a, f, g, h |
| 8424253X | 30A, 480VAC | a, f, g, h |
| 8425120X | 20A, 120/208VAC | a, b, f, g, h |
| | | |

| 8425126X | 20A, 120/208VAC | a, b, f, g, h |
|--|------------------|---------------|
| 8425150X | 20A, 277/480VAC | a, b, f, g, h |
| 8425224X | 30A, 120/208VAC | a, b, f, g, h |
| 8425250X | 30A, 277/480VAC | a, b, f, g, h |
| 8425321X | 60A, 120/208VAC | a, b, f, g, h |
| 8425358X | 60A, 277/480VAC | a, b, f, g, h |
| 8425457X | 100A, 277/480VAC | a, b, f, g, h |
| 8425326X | 60A, 120/208VAC | a, b, f, g, h |
| 8425336X | 60A, 250VAC | a, b, f, g, h |
| 8424120X | 20A, 250VAC | a, f, g, h |
| 8424150X | 20A, 480VAC | a, f, g, h |
| 8424250X | 30A, 480VAC | a, f, g, h |
| 8424316X | 60A, 125VAC | a, f, g, h |
| 8424326X | 60A, 125-250VAC | a, f, g, h |
| 8424336X | 60A, 250VAC | a, f, g, h |
| 8424311X | 60A, 125VAC | a, f, g, h |
| 8424321X | 60A, 250VAC | a, f, g, h |
| 8424331X | 60A, 250VAC | a, f, g, h |
| 8425417X | 100A, 125VAC | a, f, g, h |
| 8425427X | 100A, 120/208VAC | a, f, g, h |
| 8425437X | 100A, 250VAC | a, f, g, h |
| 8424417X | 100A, 125VAC | a, b, f, g, h |
| 8424427X | 100A, 250VAC | a, b, f, g, h |
| 8424437X | 100A, 250VAC | a, b, f, g, h |
| 8424123X | 20A, 250VAC | a, b, f, g, h |
| 8424153X | 20A, 480VAC | a, b, f, g, h |
| 8424223X | 30A, 250VAC | a, b, f, g, h |
| 8424225X | 30A, 480VAC | a, b, f, g, h |
| Note: Where X is any digit 0-9. | | |
| Power inlet | Rating | Code |
| 8445234X | 30A, 250VAC | a, b, f, g, h |
| 8445334X | 60A, 250VAC | a, b, f, g, h |
| 8444214X | 30A, 125VAC | a, f, g, h |
| 8444224X | 30A, 250VAC | a, f, g, h |
| 8444234X | 30A, 250VAC | a, f, g, h |
| 8444314X | 60A, 125VAC | a, f, g, h |
| 8444324X | 60A, 250VAC | a, f, g, h |
| | | |

| | | |
|----------|-----------------|---------------|
| 84441241 | 20A, 250VAC | a, f, g, h |
| 84441541 | 20A, 480VAC | a, f, g, h |
| 84442541 | 20A, 480VAC | a, f, g, h |
| 8444334X | 60A, 250VAC | a, b, f, g, h |
| 8443124X | 20A, 250VAC | a, b, f, g, h |
| 8443224X | 30A, 250VAC | a, b, f, g, h |
| 8445215X | 30A, 125VAC | a, b, f, g, h |
| 8445225X | 30A, 120/208VAC | a, b, f, g, h |
| 8445235X | 30A, 250VAC | a, b, f, g, h |
| 8445315X | 60A, 125VAC | a, b, f, g, h |
| 8445325X | 60A, 120/208VAC | a, b, f, g, h |
| 8445335X | 60A, 250VAC | a, b, f, g, h |
| 8445210X | 30A, 125VAC | a, b, f, g, h |
| 8445220X | 30A, 120/208VAC | a, b, f, g, h |
| 8445230X | 30A, 250VAC | a, b, f, g, h |
| 8445120X | 20A, 120/208VAC | a, b, f, g, h |
| 8445125X | 20A, 120/208VAC | a, b, f, g, h |
| 8445150X | 20A, 277/480VAC | a, b, f, g, h |
| 8445250X | 30A, 277/480VAC | a, b, f, g, h |
| 8445350X | 60A, 277/480VAC | a, b, f, g, h |

Where X is any digit 0-9.

Codes:

- a. Grounded type.
- b. Provided with neutral pole.
- c. Suitable for wet and damp locations.
- d. Not intended for current interruption.
- e. Surface mount type.
- f. Panel mount type.
- g. Mounting means not grounded. Separate grounding connection required.
- h. Provided with cap (or cover).
- i. For use with 75 C conductors only, 75 C ampacity.
- j. For installation in series with switches; not for closing or opening circuits under load.
- k. Fused for supplementary branch circuit protection.

Last Updated on 2002-07-29

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2006 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

