



Maximum Leakage Current (L-G) @115VAC/60Hz	Maximum Leakage Current (L-G) @250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm sys.) Freq. - MHz						Min. differential mode insertion loss (L-L) (dB in 50 ohm sys.) Freq. - MHz									
		.05	.10	.15	.50	1.0	5.0	10	30	.05	.10	.15	.50	1.0	5.0	10	30
0.25 mA	0.45 mA	10	15	15	25	30	40	40	30	2	5	3	35	45	40	40	30

Note 1: Recommended diameter for thru-hole (screw/nut combination) hardware mounting method. Other methods will require holes with different dimensions and parameters.

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.				DIMENSIONS IN MILLIMETERS		TITLE Module	
				DRAFT BY: JPC		DATE: 5-5-2003	
				DRAFTING APPROVAL: JPC		DATE: 5-5-2003	
				PART NUMBER: 83511420			
A		Added dimension information to cutout screw holes and Note 1.		4/09/12		DDF	
REV		CHANGE DESCRIPTION		DATE		INITIALS	
				MATERIAL:		DO NOT SCALE	
						SHEET 1 OF 1	
				INTERPOWER CORPORATION			