## North American Cord Set Configurations This information is in accordance with UL817 and CSA C22.2 No. 21-95

	IEC 60320 Connectors										
	0.2A Family	2.5 Fan	5A nily	6A Family	15A North American Family			20A North American Family			
	Class II	Class I	Class II	Class II	Class I Cla		Class II	Class I		Class II	
North American NEMA Plugs	C1	C5	<b>C7</b>	C9	C13	C15	C15A	C17	C19	C21	G23
(s • 0 ) 5-15P	Х	<b>√</b>	X	X	1	<b>✓</b>	<b>✓</b>	Х	<b>√</b>	<b>✓</b>	X
<b>□ 1-15P</b>	1	X	1	1	X	X	X	<b>✓</b>	X	X	1
- I 5-20P	X	>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	>	<b>&gt;</b>	X
6-15P	X	<b>√</b>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	<b>&gt;</b>	<b>✓</b>	X
6-20P	X	<b>✓</b>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	<b>✓</b>	<b>✓</b>	X
L5-15P	X	<b>√</b>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	<b>✓</b>	<b>√</b>	X
L5-20P	X	<b>√</b>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	<b>✓</b>	<b>√</b>	X
L5-30P	X	<b>√</b>	X	X	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	<b>√</b>	<b>√</b>	X
L6-15P	X	<b>√</b>	X	X	1	<b>✓</b>	<b>√</b>	X	<b>√</b>	✓	X
L6-20P	X	<b>√</b>	X	X	1	<b>✓</b>	<b>√</b>	X	<b>√</b>	✓	X
L6-30P	X	<b>√</b>	X	X	1	<b>√</b>	1	X	<b>√</b>	✓	X

✓ Allowed per UL817 and CSA C22.2 No. 21-95

Not allowed per UL817 and CSA C22.2 No. 21-95

NOTE: For cable type, size, and material refer to end use product application. A cord set is defined as an assembly consisting of one flexible cable or cord fitted with one plug and one connector.

