

Guide to International Cable

For specifications on these and more international and North American cables, please visit our web site at www.interpower.com



Order online:
www.interpower.com

P.O. Box 115, Oskaloosa, IA 52577 (USA)
Call: (641) 673-5000 Fax: (641) 673-5100
E-mail: info@interpower.com


Toll-free (U.S./Can./P.R./V.I.)
Call toll-free: (800) 662-2290
Fax toll-free: (800) 645-5360




Rev. 6-10

North American Fillerless Cable

The advantage of fillerless cable is the elimination of paper fillers. This eliminates the need to remove the filler when the cable is terminated, saving time and eliminating the possibility of assembler injury. Note, fillerless cable is smaller in diameter than conventional cable with similar ratings. Fillerless cable is available from stock in white, black, gray, tan, yellow, and orange. Call (800) 662-2290 for other colors available by special order.



SPT-2
86030260: 2 x 18AWG, 10A/300V
86030270: 2 x 16AWG, 13A/300V



SPT-3
Size ranges: 3 x 18–3 x 12AWG
Rating: 10–25A/300V
86030340: 3x18AWG, 10A



SJT, SVT
Size ranges: 3 x 18–3 x 12AWG
Rating: 10–25A/300V
86030230: 3x18AWG, 10A, SJT



SJT, SVT, SJTO
Size ranges: 3 x 18–3 x 10AWG
Rating: 10–30A/300V
86030100: 3 x 18AWG, 10A, SJT

North American Cable (with filler)

Colors available by special order. Please call our Customer Service Department at (800) 662-2290 for more information.



SJT, SJTW
86030240: 2 x 18AWG, 10A/300V, SJT
86030250: 2 x 16AWG, 13A/300V, SJT



SJT
Size ranges: 3 x 18–3 x 12AWG
Rating: 10–25A/300V
86010450: 3 x 18AWG, 10A



SJT
86030380: 4 x 12AWG, 20A/300V



SJT (1 cable)
86030390: 5 x 12AWG, 16A/300V

North American Rubber Cable (with filler)



SOOW
Size ranges: 3 x 14–3 x 8AWG
Rating: 18–40A/600V
86010600: 3 x 14AWG, 18A, SOOW



SOW, SOOW
86010710: 4 x 10AWG, 25A/600V, SOW
86010720: 4 x 8AWG, 35A/600V, SO



SO/SOW, SOOW, SEO
Size ranges: 5 x 10–5 x 2AWG
Rating: 20–64A/600V
86010661: 5 x 10AWG, 20A, SOOW

North American Oil Resistant Cable



ST/STO
86030710: 3 x 14AWG, 18A/600V
86030700: 3 x 12AWG, 25A/600V

Flexible North American Cable

Added flexibility and durability! The North American cable below features a very flexible TPE (thermoplastic elastomer) jacket. This jacket compound is a high molecular density PVC. It is resistant to ultra-violet light, abrasion, extreme cold, and most chemicals. Cable meets and exceeds UL62 tensile strength requirements. These properties are excellent for applications that brave the elements.



SJEOW/SJTO
86030610: 2 x 16AWG, 13A/300V
86030620: 2 x 14AWG, 18A/300V



SJEOW/SJTOW
Size ranges: 3 x 18
Rating: 10–25A/300–600V
86030560: 3 x 18AWG, 10A/300V, SJEOW/SJTOW

North American Shielded Cable

The North American shielded cable below is PVC jacketed and available in black with BWG or BBG/Y* color coding. It utilizes PVC insulation, paper filler, and an aluminum foil shield with a drain wire and tissue paper separator.



SJT, SVT
Size ranges: 3 x 18–3 x 12AWG
Rating: 10–25A/300V
86024060: 3 x 18AWG, 10A, SJT

International Harmonized Cable



H05VVF
86020160: 2 x 0.75mm², 6A/300/500V



H05VVF
Size ranges: 3 x 0.75–4.00mm²
Rating: 6–32A/300/500–750V
86020020: 3 x 0.75mm², 6A/300/500V



H05VVF
86020190: 5 x 1.00mm², 10A/300/500V
86020200: 5 x 1.50mm², 16A/300/500V
86020210: 5 x 2.50mm², 20A/300/500V

International Rubber Cable



H07RNF
86020300: 3 x 1.50mm², 16A/450/750V
86020310: 3 x 2.50mm², 25A/450/750V
86020320: 3 x 4.00mm², 32A/450/750V



H07RNF
Size ranges: 5 x 2.50–35.00mm²
Rating: 26–135A/450/750V
86020410: 5 x 2.50mm², 26A

International Shielded Cable

The international shielded cable below is PVC jacketed and available in black. It utilizes aluminum braided wire.



S05VC4VF
86021030: 3 x 1.00mm², 10A/300/500V
86021040: 3 x 1.50mm², 16A/300/500V

Cable Marking & Packaging Services

Special delivery? No problem. We offer the following cable marking and packaging services. Special carton marking or labeling is also available. Call our Customer Service Department at (800) 662-2290 for a quotation on these services.



Wrap Label



Hot Stamp



Custom Flags



Grounding Reliability



Coil



Cord Bundle:
25 standard to a bundle



Hank



Cable Ties



Box



Bag



Custom Cable lengths

Cutting and stripping capabilities in our Oskaloosa, IA factories. We cut and strip to any length. The machine at left strips and crimps cable for a uniform strip. Call (800) 662-2290 for more information.

Order direct from our warehouse in Oskaloosa, IA,

- No minimum order requirements
- Same day shipment available for stock item orders received by 6:00 p.m. Central Time
- Most items available from stock
- Free evaluation samples
- Assembly services available
- Technical support available