


Connect to North America



www.interpower.com
formerly Panel Components Corporation






P.O. Box 115, Oskaloosa, IA 52577 (USA)
Call: (641) 673-5000 Fax: (641) 673-5100
E-mail: info@interpower.com

Toll-free (U.S./Can./P.R./V.I.)
Call toll-free: (800) 662-2290
Fax toll-free: (800) 645-5360



Rev. 8-05

Plugs and receptacles by rating

Rating	NEMA Configuration	Style	Plug	In-line Connector	Receptacle Single	Receptacle Duplex	Dust-Resistant Inlet	Flanged Inlet	Flanged Outlet	Recommended Cable	
15A 125VAC	(socket view)									For 15A devices: PVC: 86030180 3x14AWG, SJT, 18A/300VAC, 9.4mm O.D., wiring code: brown, blue, green/yellow 	
		5-15	Straight blade	88030100	88030110	88031010	88030070	88031100	88031040		88031030
		5-15	Straight blade, Hospital	88030270	88030280	88030290	88030890	—	—		—
15A 250VAC		L5-15	Locking	88030240	88030250	88031210	88031220	88031140	88030480	88030490	TPE: 86030530 3x14AWG, SJEOW/SJTOW, 18A/300VAC, 9.4mm O.D., wiring code: black, white, green 
		6-15	Straight blade	88030200	88030210	88030610	88030590	88031110	88030440	88030450	
		6-15	Straight blade, Hospital	88030370	88030380	—	88030830	—	—	—	
20A 125VAC		L6-15	Locking	88030220	88030230	88030630	88030640	88031150	88030650	88030660	For 20A devices: PVC: 86030310 3x12AWG, SJT, 25A/300VAC, 11.1mm O.D., wiring code: brown, blue, green/yellow 
		5-20	Straight blade	88030120	88030130	88030080	88030430	88031120	88030460	88030330	
		5-20	Straight blade, Hospital	88030390	88030400	88030580	88030940	—	—	—	
20A 250VAC		L5-20	Locking	88030140	88030150	88030300	—	—	88030500	88030510	TPE: 86030500 3x12AWG, SEOW/STOW, 25A/600VAC, 16.1mm O.D., wiring code: black, white, green 
		6-20	Straight blade	88030180	88030190	88030620	88030600	88031130	88030470	88030030	
		6-20	Straight blade, Hospital	88030410	88030420	—	—	—	—	—	
30A 125VAC		L6-20	Locking	88030160	88030170	88031080	—	—	88030090	88030530	For 30A devices: PVC: 86030430 3x10AWG, SJT, 30A/300VAC, 15.1mm O.D., wiring code: black, white, green 
		L5-30	Locking	88031070	88031160	88031170	—	—	88030540	88030550	
30A 250VAC		L6-30	Locking	88030310	88030320	88031180	—	—	88030560	88030040	TPE: none