


[HOME](#)
[ABOUT](#)
[SERVICES](#)
[INDUSTRIES](#)
[SHOP CSA](#)
[LOG IN](#)
[Home](#) » [Services](#) » [Testing & Certification](#) » [Certified Product Listing](#) » **Certificate Record**

Certificate Record

Customer	Class	File Number
Feller GmbH Waerndorferstrasse 3, Guenselsdorf Austria 2525	5842-02 CORD SETS-Power Supply Cords	015075_0_000

Quick Links

[Certification Marks and Labels](#)
[Certified Product Listing](#)
[CSA Communities](#)
[Request a Quote](#)

TO THE REQUIREMENTS OF CSA STD C22.2 NO 21-95, NO 42-M1987:

- Power supply cords, consisting of special use plug caps or female connectors, moulded onto flexible cords rated 60 deg C, having ratings as listed below.

Cat. No.	Configuration	Flexible Cord		Rating		
		Type(s)	Size (AWG)	Volts	Amps	
498G,	5-15P	SVT, SJT	18	125	10	
498/1,		SJT	17	125	12	
498/2,		SVT, SJT	16	125	13	
498/3,			14	125	15	
498/4,						
498/5,						
498/6,						
498/7, 498/8, 498G						
N1/15	1-15P	SPT-2,	18	125	10	
		SVT, SJT,				
		SPT-1	16	125	13	
		SJT, SVT	17	125	12	
		SVT, SJT	14	125	15	
		SJT				
N1/15L	1-15P	SVT	18	125	10	
		SVT	17	125	12	
498/3	1-15P	SPT-1,	18	125	10	
		SPT-2,				
		SVT, SJT,	16	125	13	
		SPT-2, SJT				
498A,	5-15P	SJT	16	125	13	
498B		SJT, ST	14	125	15	
14/30A, 14/30B	14/30P	DRT	10	125/250	30	
N5/20	5-20P	SJT	12	125	20	
		SJT, ST	14	125	16	
N6/20	6-20P	SJT	12	250	20	
		SJT, ST	14	250	16	
C20, C20W	SP, 2-P, 3-W	ST, SJT	14	250	16	
		SJT	12	250	20	
C8G	Plug	SVT, SPT-2	18	125	7	
				250	2.5	

Cat. No.	Configuration	Flexible Cord		Rating	
		Type(s)	Size (AWG)	Volts	Amps
0812W	2-P, 2-W	SPT-1	18	125	2.5
C14R,	SP, 2-P, 3-W	SVT, SJT	18	250	10
C14		SJT	16	250	13
C14G,	SP, 2-P, 3-W	SVT, SJT	18	250	10
C16G,		SJT	16	250	13
C14G2S					
C14G	2-P, 3-W	SJT	14	250	15
0823	2-P, 2-W	SPT-1	18	125	3.5
C15,	2-P, 3-W	SJT	18	250	10
C15W,		SJT, ST	16	250	13
C15A		SJT	14	250	15
C15M	Conn, 2-P, 3-W	SJT	18	250	10
		SJT	16	250	13
		SJT	14	250	15
C15L	Conn, 2-P, 3-W	SJT	18	250	10
		SJT	16	250	13
		SJT	14	250	15
C18G	2-P, 2-W	SJT, SVT	18	250	10
C19,	2-P, 3-W	SJT, ST,	14	250	16
C19W,		SJOW, SJT	12	250	20
C19L					
136, 136W	2-P, 3-W	SJT	18	250	10
		SJT, ST	16	250	10
				125	13
C9, C9W,	2-P, 2-W	SPT-2, SVT	18	250	10
C9PW					
C21,	2-P, 3-W	SJT	14	250	16
C21W,			12	250	20
C21L			14	250	15

Note: Sold only to manufacturers for assembly of Certified electrical equipment.

- Special use power supply cords consisting of an attachment plugs moulded on the flexible cord with the following electrical ratings:

Plug Cap	Flexible Cord		Rating	
	Type (s)	Size (AWG)	Volts	Amps
Cat No				
W1G	SVT	18	125	10
W2G	SVT	18	125	10

- Hospital Grade Power Supply cords, consisting of attachment plugs moulded onto flexible cords rated 60 deg C, having rating as listed below:

Plug Cap	Flexible Cord			Rating	
	Configuration	Type(s)	Size (AWG)	Volts	Amps
Cat No					
HG	5-15P	SJT	18	125	10
		SJT	16	125	13
		SJT, ST	14	125	15
		SJT	12	125	15
HG	5-20P	SJT	12	125	20

TO THE REQUIREMENTS OF CAN/CSA-C22.2 NO 21-M95 AND CAN/CSA-C22.2 NO 182.3-M1987:

- Power Supply Cords, consisting of the following special-use connectors moulded onto flexible cords rated 60°C, having ratings as listed below:

Cat. No.	Configuration	Flexible Cord		Rating	
		Type(s)	Size (AWG)	Volts	Amps

		SVT, SJT,	18	250	10
		SVT, SJT	17	250	12
C13WK	2-P, 3-W	SVT, SJT	18	250	10
			17	250	12
			16	250	13
C13M	2-P, 3-W	SJT	18	250	10
			17	250	12
			16	250	13
			14	250	15
C13N	2-P, 3-W	SVT, SJT	18	250	10
C17, C17W	2-P, 2-W	SVT, SJT,	18	250	10
		SVT, SJT	17	250	12
13VA, 13VB, 13VWN	2-P, 3-W	SJT	18	250	10
			17	250	12
			16	250	13
			14	125	15
13V, 13VW	2-P, 3-W	SJT	18	250	10
			17	250	12
			16	250	13
			14	125	15
17V	2-P, 2-W	SJT	18	250	10
			16	250	13
C7	2-P, 2-W	SJT	18	250	2.5
C7*, C7P, C7W, C7PW	2-P, 2-W	SVT,	18	125	7
		SPT-2, SJT			
13VN	2-P, 3-W	SJT	18	250	10
			16	250	13
			14	125	15
C5, C5W	2-P, 3-W	SVT	18	127	7
13VL	2-P, 3-W	SJT	18	250	10
			17	250	12
			16	250	13
			14	125	15

Notes:

1. Sold only to manufacturers for assembly of Certified electrical equipment.
2. C7* is the alternate construction of C7.

THE FOLLOWING COMPLIES WITH THE REQUIREMENTS OF CSA STD C22.2 NO 21-M1984, ECN 436C:

- Moulded PVC, parallel-blade and grounding type attachment plug cap, Types MC3 and 498/13, moulded to suitable lengths of No 18 AWG, Types SVT or SJT, 3-conductor, flexible cord, or moulded to suitable lengths of No 16 AWG, Type SJT, 3-conductor, flexible cord.
- Moulded PVC, attachment plug caps, parallel-blade, Types MC2 and 498/3, moulded to suitable lengths of No 18 AWG, Types SPT-1, SPT-2, SVT or SJT flexible cord, or moulded to suitable lengths of No 16 AWG, Type SPT-2 or SJT flexible cord.
- Moulded PVC special-use pull-off plugs, 2-pole, 2-wire, moulded to a suitable length of No 18 AWG, Type SPT-1 flexible cord, Type 0812W, 2.5A, 125V; Type 0823, 3.5A, 125V.
- Moulded PVC special-use pull-off plugs, 2-pole, 3-wire grounding type, Type C15, moulded to suitable lengths of No 16 AWG Type SJT or ST flexible cord, 10A, 125V or 10A, 250V ac, Type C19, moulded to suitable lengths of No 14 AWG, Type ST flexible cords, 16A, 125V ac or 16A, 250V ac.

- Moulded PVC special-use attachment plugs, 2-pole, 3-wire grounding type, Type C20, moulded to suitable lengths

AWG No.	Flexible Cord Type(s)	Rated
12	SJT	20A, 250V ac
14	SJT, ST	16A, 250V ac
14	ST	16A, 125V ac

- Moulded PVC special-use attachment plugs, 2 pole, 3 wire grounding type, Type C20W moulded to a suitable length of No. 12AWG, Type SJT flexible cord, 20A, 250V ac.
- General-use attachment plug cap, 2-pole, 3-wire grounding type, Type N5/15, moulded to a suitable length of No 14 AWG, Type SJT flexible cord, 15A, 125V ac.
- General-use attachment plug cap, 2-pole, 3-wire grounding, Type N5/20, moulded to a suitable length of No 12 AWG, Type SJT flexible cord, 20A, 125V ac.
- General-use attachment plug cap, 2-pole, 3-wire grounding, Type N5/15, moulded to a suitable length of No 14 AWG Type SJT flexible cord, 15A, 250V ac.
- General-use attachment plug cap, 2-pole, 3-wire grounding, Type N6/20, moulded to a suitable length of No 12 AWG Type SJT flexible cord, 20A, 250V ac.
- Special-use pull-off plug, 2-pole, 3-wire grounding type, Types 136 or 136W, moulded to suitable lengths of No 16 or 18 AWG, Type SJT or ST flexible cord, 10A, 250V ac.
- Special-use attachment plug cap, 2-pole, 3-wire grounding, Type 22/V or 22/VW, moulded to suitable lengths of No 18 AWG, Type SVT or SJT flexible cord, 10A, 125V ac, 1250W or 10A, 250V ac, 2500W. Note: Sold only to manufacturers for assembly of Certified electrical equipment.
- Moulded PVC special use pull-off plug, 2 pole, 2 wire, Type C17 moulded to suitable length of No. 18AWG, Type SVT or SJT flexible cord, 10A, 250V ac; Type 17V moulded to a suitable length of No. 18AWG, Type SJT flexible cord, 10A, 250V ac; Type C7 moulded to a suitable length of No. 18AWG, Type SPT-1 or SVT flexible cord, 2.5A, 250V ac.
- Moulded PVC special use pull-off plug, 2 pole, 3 wire grounding type, Type C15W moulded to a suitable length of No. 16AWG, Type SJT or ST flexible cord, 10A, 125V ac, or 10A, 250V ac; Types C13 and C13W moulded to a suitable length of No. 18AWG, Type SJT or SVT flexible cord, 10A, 250V ac; Type 13V moulded to a suitable length of No. 18AWG, Type SJT flexible cord, 10A, 250V ac or No. 16AWG, Type SJT flexible cord, 13A, 250V ac.

Note: Sold only to manufacturers for assembly of Certified electrical equipment.

- Power Supply Cords, consisting of configuration 5-15P attachment plug cap, Type 5/15A, moulded to a suitable length of:
 - No 14 AWG, Type SJT, ST flexible cord, 15 A, 125 V ac.
 - No 16 AWG, Type SJT flexible cord, 13 A, 125 V ac.
 - No 18 AWG, Type SJT flexible cord, 10 A, 125 V ac.
- Power Supply Cords, consisting of configuration 5-20P attachment plug cap, Type 5/20A, moulded to a suitable length of No 12 AWG, Type ST flexible cord, 20 A, 125 V ac.
- Power Supply Cords, consisting of configuration 6-20P attachment plug cap, Type 6/20A, moulded to a suitable length of No 12 AWG, Type SJT flexible cord, 20 A, 250 V ac.

Note: The above products are sold only to manufacturers for assembly to Certified electrical equipment

- Locking type General Use Power Supply Cords, consisting of attachment plug caps, moulded onto suitable lengths of flexible cords, Cat. Nos. and Ratings as listed below:

Cat No	Configuration	Flexible Cord Type	Size (AWG)	Ratings	
				Volts	Amps
L5/30	L5-30P	SJT, SJTW	12	125	20
		SJT, SJTW,	10	125	30
		SOOW	8	125	30
		SOOW			

L6/30	L6-30P	SJT, SJTW	12	250	20 and 25
		SJT, SJTW,	10	250	30
		SOOW	8	250	30
		SOOW			
L6/20	L6-20P	SJT, SJTW	14	250	15
		SJT, SJTW	12	250	20
		SJT, SJTW,	10	250	20
		SOOW			
L5/20	L5-20P	SJT, SJTW	14	125	15
		SJT, SJTW	12	125	20
		SJT, SJTW,	10	125	20
		SOOW			

Note: The above products are sold only to manufacturers for assembly to Certified electrical equipment.

TO THE REQUIREMENTS OF CSA STD C22.2 NO 21-M95, No. 182.3-M1982, ECN 278D, 436, 436A TO 436D:

- Power Supply Cords consisting of a special-use attachment plug cap, 2-pole, 3-wire grounding:
 - Type C14 (Left-angled version), Type SJTX18, 16 and 14 AWG and SVT3X18AWG flexible cord, rated 10 A/250 V ac (18 AWG), 13 A/250 V (16 AWG) and 14 A/250 V (14 AWG) or No. 17 AWG Type SJT flexible cord, 12 A 250V.
 - Type C14R (Right-angled version), moulded to a suitable length of No. 18 Type SVT or No. 18 AWG or No. 16 AWG Type SJT flexible cord, 10 A, 250 V ac or No. 17 AWG Type SJT flexible cord, 12 A 250V.
 - Type C14G, moulded to a suitable length of No. 18 AWG Type SJT flexible cord or No. 18 AWG Type SVT flexible cord, 10 A, 250 V ac or No. 16 AWG Type SJT flexible cord, 13 A, 250 V ac or No. 17 AWG Type SJT flexible cord, 12 A 250V.
 - Type C18G, 2-pole, 2-wire, moulded to a length of 2 X 18 AWG, Type SJT or SVT flexible cord, 10 A, 250 V ac. or 2 x 17 AWG Type SJT flexible cord, 12 A 250V.

Note: Sold only to manufacturers for assembly to Certified electrical equipment.

TO THE REQUIREMENTS OF CAN/CSA-C22.2 No 21-M95 AND 42-M1999:

- Power Supply Cords, consisting of attachment plug caps moulded onto flexible cords rated 60°C, having ratings as listed below.

Cat No.	Cord AWG	Type	Current, Amperes	Volts
5/15	16, 14	SJT (for all AWG sizes)	13, 15	125
		ST (for 16, 14, 12 AWG)		
6/15	16, 14	SJT (for all AWG sizes)	13, 15	250
		ST (for 16, 14, 12 AWG)		
N5/15	18, 16, 14, 12	SJT (for all AWG sizes)	10, 13, 15, 15	125
		ST (for 16, 14, 12 AWG)		
N6/15	18, 16, 14, 12	SJT (for all AWG sizes)	10, 13, 15, 15	250
		ST (for 16, 14, 12 AWG)		
N5/20	18, 16, 14, 12	SJT (for all AWG sizes)	10, 13, 15, 20	125
		ST (for 16, 14, 12 AWG)		
N6/20	18, 16, 14, 12	SJT (for all AWG sizes)	10, 13, 15, 20	250
		ST (for 16, 14, 12 AWG)		
498A	16, 14	SJT (for all AWG sizes)	13, 15	125
		ST (for 16, 14, 12 AWG)		
498B	16, 14	SJT (for all AWG sizes)	13, 15	125
		ST (for 16, 14, 12 AWG)		

Note: Sold only to manufacturers for assembly to certified electrical equipment.

- Power Supply Cords, consisting of attachment plugs moulded onto flexible cords, having rating as listed below:

Cat No.	Type	Cord AWG	Current, Amperes	Volts
5/15A	SJT (for all AWG sizes)	18, 16, 14, 12	10, 13, 15, 15	125
	ST (for 16, 14, 12 AWG)			

6/15A	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 15	250
5/20A	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 20	125
6/20A	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 20	250
5/15B	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 15	125
6/15B	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 15	250
5/20B	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 20	125
6/20B	SJT (for all AWG sizes) ST (for 16, 14, 12 AWG)	18, 16, 14, 1210, 13, 15, 20	250

Note: The above products are sold only to manufacturers for assembly to Certified electrical equipment.

TO THE REQUIREMENTS OF CAN/CSA-C22.2 No 0-M91 AND CSA Std. 21-95:

- Hospital Grade Power Supply Cords, consisting of attachment plugs moulded onto flexible cords rated 60 deg C, having rating as listed below:

Cat No.	Type Cord	AWG	Current, Amperes	Volts
N5/15 Hospital Grade	SJT	18, 16, 14, 12	10, 13, 15, 15	125
	ST	14, 12		
N6/15 Hospital Grade	SJT	18, 16, 14, 12	10, 13, 15, 15	250
	ST	14, 12		
N5/20 Hospital Grade	SJT	18, 16, 14, 12	10, 13, 15, 20	125
	ST	14, 12		
N6/20 Hospital Grade	SJT	18, 16, 14, 12	10, 13, 15, 20	250
	ST	14, 12		
HG	SJT	14, 16, 18	15, 13, 10	125
	SVT	18	10	

Note: For use only in the applicant's cord sets and power supply cords where the acceptability is determined by CSA International.

TO THE REQUIREMENTS OF CSA STD C22.2 NO 21-M90 and 42-M1984:

- Moulded polyvinyl chloride, parallel-blade attachment-plug cap, Type 4190 and 4191, moulded to a suitable length of No 17 or 18 AWG, Types SVT or SJT flexible cord.
- Moulded polyvinyl chloride, parallel-blade grounding type attachment-plug cap, Types 4390 and 1140, moulded to a suitable length of No 18 AWG, Types SVT or SJT flexible cord.
- Power Supply Cords, consisting of a moulded pvc parallel-blade grounding type attachment plug cap Type 4392, moulded to a suitable length of Type SJT flexible cord No. 18 AWG, 10 A 125 Vac or No. 16 AWG, 13 A 125 Vac or No. 14 AWG, 15 A 125 Vac

Note: The power supply cords are sold only to manufacturers for the assembly of Certified electrical equipment.

- Power interconnection cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Type 6002B, 6202B or 6004B, moulded to a suitable length of 2-conductor Type SVT No 18 AWG flexible cord, 6A, 250V; Type 408B, 409B, 608B or 609B, moulded to a suitable length of 2-conductor Type SVT or SJT No 18 AWG flexible cord, 10A, 250V.
- Power interconnection cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Type 6002, 6202 or 6004, moulded to a suitable length of 3-conductor Type SVT No 18 AWG flexible cord, 6A, 250V; Type 408, 409, 608 or

609, moulded to a suitable length of 3-conductor Type SVT or SJT No 18 AWG flexible cord, 10A, 250V.

- Power interconnecting cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Type 6370, moulded to a suitable length of 2-conductor Type SVT No. 18 AWG flexible cord 2A, 125V ac or 250V ac.
- Power interconnection cords, consisting of a moulded polyvinyl chloride special-use connector Type 5320 or 5311, moulded to a suitable length of 2 conductor Type SVT No. 18 AWG flexible cord, 2.5A, 125V ac or 250V ac.
- Power inter-connection cord, consisting of a moulded pvc special-use connector Type 2530 and 2512 moulded to flexible cord Type SVT No 18 AWG, 2.5A, 250V ac.
- Power Interconnecting cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Types 2510, 2511, 2514, 2702, 2707, 2711, 2712 and 2730, 2731 moulded to a suitable length of a 2-conductor Type SVT No. 18 AWG flexible cord 2.5 A, 250 Vac.
- Power Interconnecting cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Type 2706, moulded to a suitable length of 2-conductor Type SJT No. 18 AWG flexible cord 2.5 A, 250 Vac.
- Power Interconnecting cords, consisting of a moulded polyvinyl chloride special-use attachment plug cap Type 2705, moulded to a suitable length of 3-conductor Type SVT No. AWG flexible cord 2.5 A, 250 Vac.

Notes:

1. The power interconnection cords are sold only to manufacturers of electrical equipment who will incorporate them as part of a Certified device.
2. The assemblies are for use only as power interconnecting cords between two Certified electrical devices, where the acceptability of the combination has been determined by CSA Group.

- Power Supply Cord, configuration consisting of 5-15P attachment plug cap molded onto flexible cord, Type SJT, 3/18, 3/17, 3/16 and 3/14 AWG, and Type SVT, 3/17 and 3/18 AWG. Maximum ratings: 125 V and 60° C, 10 A with 18 AWG, 12 A with 17 AWG, 13 A with 16 AWG and 15 A with AWG 14 as follows: Straight Plug Style: Cat. No: 498G; Angled Version Style: Cat. No's: 498/1, 498/2, 498/3, 498/4, 498/5, 498/6, 498/7, 498/8.

Note: Sold only to manufacturers for assembly to certified electrical equipment.

/ts

CSA Group Web Sites	CSA Group Sites	Information For...	Corporate	About CSA Group
CSA Group Bayern GmbH	CSA Communities	Manufacturers	Privacy	CSA Group is an independent, not-for-profit member-based association dedicated to advancing safety, sustainability and social good. We are an internationally-accredited standards development and testing & certification organization. We also provide consumer product evaluation and education & training services. Our broad range of knowledge and expertise includes: industrial equipment, plumbing & construction, electro-medical & healthcare, appliances & gas, alternative energy, lighting and sustainability. The CSA mark appears on billions of products around the world.
CSA Group Seattle	CSA Registries	Members	Terms of Use	
CSA Group Testing UK Ltd.	OHS Portal	Government, Regulators & AHJs	Service Agreement	
CSA Group UK – Transportation	Public Review	Retailers / Importers / Exporters	CSA Product Certification Scheme	
ICM GmbH	Shop CSA	Consumers	Evidence of Insurance	
	CSA Group Videos		OHS Corporate Policy	
			Environment	
			Corporate Policy	

Copyright © 2017 - CSA Group. All Rights Reserved.
[Contact Us](#) [Site Map](#) [Accessibility](#)