



RTRT.E111198 Receptacles for Plugs and Attachment Plugs

Page Bottom

Receptacles for Plugs and Attachment Plugs

See General Information for Receptacles for Plugs and Attachment Plugs

ACTUANT ELECTRICAL, DBA MARINCO
N85 W12545 WESTBROOK CROSSING
MENOMONEE FALLS, WI 53051 USA

E111198

Attachment plugs, 150 AMP, 600V, single pin and sleeve locking type, Cat. No. CLMM.

400 AMP, 600V, single pin and sleeve locking type, Cat. Nos. CL40MB, CLS40MB, CLS1840MB, 3240211, 3240221, 3240231, 3240241, 3240251, 3240261, 3240271.

Cord connectors, 150 AMP, 600V, single pin and sleeve locking type, Cat. No. CLMF.

400 AMP, 600V, single pin and sleeve locking type, Cat. Nos. CL40FB, CLS40FB, CLS1840FB.

Receptacle, 15AMP, 125 V, grounding type, single, Cat. Nos. 5254.

Receptacle, 20AMP, 125 V, grounding type, single, Cat. Nos. 5354.

Receptacle, 15AMP, 250 V, grounding type, single, Cat. No. 5654.

Receptacle, 20AMP, 250 V, grounding type, Cat. Nos. 5454.

Receptacle, 20AMP, 125 V, grounding type, Cat. Nos. 205CRR, 205R, 205RIG.

20AMP, 250 V, grounding type, Cat. Nos. 206CRR, 206R, 206RIG, 2015R, 2015CRR.

20AMP, 277V, grounding type, Cat. No. 207R.

20AMP, 480 V, grounding type, Cat. Nos. 208R.

20AMP, 600 V, grounding type, Cat. No. 209R.

30AMP, 125 V, grounding type, Cat. Nos. 305CRR, 305R, 305RIG.

30AMP, 250 V, grounding type, Cat. Nos. 306CRR, 306R, 306RIG.

50AMP, 125/250 V, grounding type, Cat. Nos. 6369CR, CS6369.

50AMP, 125 V, grounding type, Cat. Nos. 6370CR, CS6370.

50AMP, 250 V, grounding type, Cat. Nos. CS8269, CS8369.

50AMP, 480 V, grounding type, Cat. Nos. CS8469, CS8169.

50AMP, 250 VDC/600 VAC, grounding type, Cat. Nos. 3769, 3771.

100AMP, 125/250 V, grounding type, Cat. No. M4100R12.

100AMP, 120/208 V, grounding type, Cat. No. M5100R9.

20AMP, 120/208 V, grounding type, Cat. Nos. 2021R, 2021CRR.

20AMP, 277/480 V, grounding type, Cat. Nos. 2022R, 2022CRR.

20AMP, 347/600 V, grounding type, Cat. Nos. 2023R, 2023CRR.

Receptacle, 20AMP, 125/250, grounding type, Cat. Nos. 2014R, 2014CRR.

Receptacle, 30AMP, 125/250V, grounding type, Cat. Nos. 3014R, 3014CRR.

Receptacle, 30AMP, 250V, grounding type, Cat. Nos. 3015R, 3015CRR.

Receptacle, 30AMP, 480V, grounding type, Cat. Nos. 3016R, 3016CRR.

Receptacle, 30AMP, 120/208V, grounding type, Cat. Nos. 3021R, 3021CRR.

Receptacle 30AMP, 277/480V, grounding type, Cat. Nos. 3022R, 3022CRR.

Receptacle 30AMP, 347/600V, grounding type, Cat. Nos. 3023R, 3023CRR.

Receptacles, 150AMP, 600 V, single pin and sleeve locking type, Cat. Nos. CLMFR, CLMFRS.

Receptacles, 400AMP, 600 V, single pin and sleeve locking type, Cat. Nos. CL40FRB, CL40FRAC, CL40FRB-BB, CL40FRSB, CLS40FRSB.

Flanged inlet, 100AMP, 125/150 V, grounding type, Cat. No. M4100B12R.

Flanged inlet, 100AMP, 120/208 V, grounding type, Cat. No. M5100B9R.

Inlets, 150AMP, 600 V, single pin and sleeve locking type, Cat. Nos. CLMMR, CLMMRS.

Inlets, 400AMP, 600 V, single pin and sleeve locking type, Cat. Nos. CL40MRB, CL40MRAC, CL40MRB-BB, CL40MRSB, CLS40MRSB.

Flanged outlet, 125V, 15A, grounding type, Cat. Nos. 5279, -CR, -WP, -WPYY, 4715, -CR, -WP, -WPYY; 125V, 20A, Grounding type Cat. Nos. 205F0, may be followed by -LD or -FORF; Cat. Nos. 5379, -CR, -WP, -WPYY, 250V, 15A, Grounding type Cat. Nos. 5679, -CR, -WP, -WPYY, 4585, -CR, -WP, -WPYY; 277V, 15A, Grounding type, Cat. No. 4785, -CR, -WP, -WPYY; 250V, 20A, Grounding type 250V, 20A, Cat. Nos. 5479, -CR, -WP, -WPYY, 206F0, may be followed by -LD or -FORF; 277V, 20A, Grounding type, Cat. No. 207F0; 125V/250V, 20A, Grounding type 2014F0, may be followed by -LD or -FORF; 250V, 20A, Grounding type Cat. No. 2015F0, may be followed by -LD or -FORF.

480V, 20A, Grounding type Cat. No. 2016F0, may be followed by -LD or -FORF; 120/208V, 20A, Grounding type, Cat. No. 2021F0, may be followed by -LD or -FORF; 480V, 20A, Grounding type, Cat. No. 208F0; 277/480V, 20A, Grounding type Cat. No. 2022F0, may be followed by -LD or -FORF; 600V, 20A, Grounding type, Cat. No. 209F0; 347/600V, 20A, Grounding type Cat. No. 2023F0, may be followed by -LD or -FORF; 125V, 30A, Grounding type Cat. No. 305F0; 250V, 30A Grounding type Cat. No. 306F0; 125/250V, 30A, Grounding type Cat. No. 3014F0, may be followed by -LD or -FORF; 250V, 30A, Grounding type Cat. No. 3015F0, may be followed by -LD or -FORF; 480V, 30A, Grounding type Cat. No. 3016F0, may be followed by -LD or -FORF; 120/208V, 30A, Grounding type Cat. No. 3021F0, may be followed by -LD or -FORF; 277/480V, 30A, Grounding type Cat. No. 3022F0, may be followed by -LD or -FORF; 347/600V, 30A, Grounding type, Cat. No. 3023F0, may be followed by -LD or -FORF.

Single pole type Stage Receptacles and Inlets, 45 degree angle, Cat. Nos. CLS45FRB, CLS45MRB, CLS45FRSB, CLS45MRSB, CLS45FRSBML, CLS45MRSBML, CLS45FRB-BB, CLS45MRB-BB.

Last Updated on 2011-08-15

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

