

ATTACHMENT PLUG

CAT. NO. C14G

(REPRESENTS CAT. NO. C18G)

FIG. 1 (M83-08418)

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. C18G is similar to Cat. No. C14G except it is a 2-wire plug.

1. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Overall dimensions 2-13/32 in (60.7 mm) long, 1-1/8 in (28.6 mm) wide, 13/16 in (20.6 mm) high. Shroud min 5/64 in (1.98 mm) thick, 21/32 in (16.6 mm) high from face.
2. Face - Recessed 21/32 in (16.6 mm) from body, overall dimensions 31/32 in (24.6 mm) by 21/32 in (16.6 mm).
3. Cord Entry - 1/2 in (12.7 mm) by 1/2 in (12.7 mm).
- *4. Cord - Listed, Type SVT or SJT, 3 conductor, No. 18, 16 or 14; **or SJT No. 17** (1409 blades only) AWG.
5. Blades - Folded from 0.037 in (0.94 mm) thick copper alloy stock, plating optional, overall length including electrical connections 1-1/32 in (26.2 mm).

Alternate - Line blade, No. 1409 and grounding blade, No. 1408, refer to Vol. 1C, Sec. 6 of this file for details.

6. Electrical Connection - Crimped to conductor, crimp length approx 3/16 in (4.7 mm).

ATTACHMENT PLUGS:

NON-STANDARD CONFIGURATION

Cat. No.	Cord AWG	Current Rating, Amperes	Voltage Rating, Volts	Section	Figure	Date
C-20	14, 12	16, 20	250	10	1	1987-01-20
C-20W	14, 12	16, 20	250	10	1	1987-01-20
C14G	18, 17, 16, 14	10, 12, 13, 15	250	15	1	1990-09-21
*						
C14R	18, 17, 16, 14	10, 12, 13, 15	250	15	2	1990-09-21
*						
C14	18, 17, 16, 14	10, 12, 13, 15	250	15	Ill. 2	1990-09-21
C16G	18, 16	10, 13	250	15	Ill. 1	1990-09-21
*						
C18G	18, 17, 16, 14	10, 12, 13, 15	250	15	1	1990-09-21
*						
C14G2S	18, 16	10, 13	250	15	1A	1990-09-21
*						
C8G	18	7	125	23	1	1998-03-03
W1G	18	10	125	27	1	2004-04-30
W2G	18	10	125	27	2, 3	2004-04-30