

CAT. NO. C5

FIG. 1 (M99-07946)

1. Line Contacts - Cat. No. RBB7994.002, refer to Vol. 1C, Sec. 11 for further details.
2. Grounding Contact - Cat. No. 650/03 manufactured by Schatz, refer to Vol. 1C, Sec. 13 for further details.
3. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Min 3/32 in (2.4 mm) thickness of molding material covers live parts, overall dimensions 2-3/16 in (55.5 mm) including cord entry. Reference may be made to Ill. 1 for further details.
4. Face - Overall dimensions approx 11/16 in (17.4 mm) by 1/2 in (12.7 mm).
5. Cord Entry - Overall dimensions 13/32 in (10.3 mm) by 13/32 in (10.3 mm) tapering to 11/32 in (8.7 mm) by 11/32 in (8.7 mm) by 7/16 in (11.1 mm) long.
- \*6. Flexible Cord - **Listed Flexible (ZJCZ/7)**. **See the following table for details.**

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SVT, SVTO, SVTOO	YES	YES

7. Premold - Molded of Recognized Component - Plastic (QMFZ2), Norly SE1GFN1, flame rating 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 1 in (25.4 mm) long, 5/8 in (15.8 mm) wide, 1/2 in (12.7 mm) high. Reference may be made to Ill. 3 for further details.
8. Marking - (Not shown) Listee's name, trade name or trademark molded on body.

CORD CONNECTORS:

## NON-STANDARD CONFIGURATION

CORD CONNECTORS:

## NON-STANDARD CONFIGURATION

Cat. No.	Cord AWG	Current Rating, Amperes	Voltage Rating, Volts	Section	Figure	Date
136	18	10	250	12	1	1988-04-27
136W	18	10	250	12	2	1988-04-27
136	16	10	250	12	1	1988-04-27
136W	16	10	250	12	2	1988-04-27
C13	18	7, 10	250	16	1	1991-01-11
C13N	18	7, 10	250	16	1 <sup>A</sup>	1991-01-11
C13M	18	10	250	16	6	1991-01-11
C17	18	7, 10	250	16	Ill. 1	1991-01-11
C13M	17	12	250	16	6	1991-01-11
C13M	16	13	250	16	6	1991-01-11
C13M	14	15	250	16	6	1991-01-11
13V	18	7, 10	250	16	2	1991-01-11
13VA	18	7, 10	250	16	Ill. 3	1991-01-11
13VB	18	7, 10	250	16	Ill. 4	1991-01-11
13VL	18	10	250	16	Ill. 5	1991-01-11
13VW	18	7, 10	250	16	3	1991-01-11
13VWN	18	10	250	16	5	1991-01-11
13VL	17	12	250	16	Ill. 5	1991-01-11
13V	16	10, 13	250	16	2	1991-01-11
13VA	16	10, 13	250	16	Ill. 3	1991-01-11
13VB	16	10, 13	250	16	Ill. 4	1991-01-11
13VN	16	13	250	16	4	1991-01-11
13VL	16	13	250	16	Ill. 5	1991-01-11
13VW	16	10, 13	250	16	3	1991-01-11
13VWN	16	13	250	16	5	1991-01-11
13V	14	15	125	16	2	1991-01-11
13VA	14	15	125	16	Ill. 3	1991-01-11
13VB	14	15	125	16	Ill. 4	1991-01-11
13VN	14	15	125	16	4	1991-01-11
13VL	14	15	125	16	Ill. 5	1991-01-11
13VW	14	15	125	16	3	1991-01-11
13VWN	14	15	125	16	5	1991-01-11
17V	18	7, 10	250	16	2	1991-01-11
17V	16	10, 13	250	16	2	1991-01-11
17V	14	15	125	16	2	1991-01-11
C13L	18	10	250	17	2	1991-09-05
C13W	18	7, 10	250	17	1	1991-09-05
C13WK	18	7, 10	250	17	Ill. 2	1991-09-05
C17W	18	7, 10	250	17	1	1991-09-05
C13L	17	12	250	17	2	1991-09-05
C13WK	17	12	250	17	Ill. 2	1991-09-05
C13WK	16	13	250	17	Ill. 2	1991-09-05
*						
C5	18	7	125	24	1	1999-05-26
C5W	18	7	125	24	2	1999-05-26