

YDPU2.E180908 - Tubing, Extruded Insulating - Component

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

CHANGYUAN ELECTRONICS GROUP CO LTD
 WOER MANSION 101 ZHUKENG COMMUNITY
 LONGTIAN STREET
 PINGSHAN DISTRICT
 SHENZHEN, GUANGDONG 518118 CHINA

E180908

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable radiation cross-linked Polyolefin tubing					
CB-1000	600	125	All except clear	-	Yes
Not-heat-shrinkable PVC tubing					
CB-300	300	105	BK or CL	-	Yes
CB-600	600	105	BK or CL	-	Yes
Flexible heat shrinkable Polyolefin tubing with liner					
CB-DWT, CB-DWT(XY)	600	125	All except clear	-	Yes
Shrinkable Polyolefin - Flexible					
CB-HFT(TM)	600	125	All except clear	-	No
CB-HFT*, CB-HFT(XY)*, CYG-MT*	300	125	All except clear	-	Yes
CB-HFT, CB-HFT(XY), CYG-MT	600	125	All except clear	-	Yes
Not heat-shrinkable silicone					
CB-SRT	600	150	All except clear	-	Yes (ID size 6.5 to 25 mm only)
Not-heat-shrinkable Polytetrafluoroethylene (PTFE) tubing					
CB-TT-L	150	200	All including clear	-	Yes

CB-TT-S	600	200	All including clear	-	Yes
CB-TT-T	300	200	All including clear	-	Yes
Heat Shrinkable FEP (fluorinated ethylene propylene) Tubing					
CYG-FEP-L	150	200	Clear	-	Yes
CYG-FEP-S	600	200	Clear	-	Yes
CYG-FEP-T	300	200	Clear	-	Yes
Flexible heat-shrinkable modified Fluoropolymer tubing					
CYG-KT	600	150	All including CL	-	Yes
CYG-KYNAR	600	150	CL	-	Yes
Shrinkable Polyolefin - Flexible					
CYG-ZHP	600	125	All except clear	-	Yes
CYG-ZHP *	300	125	All except clear	-	Yes

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

* - Designation is same for 300V and 600V. Tubing shall be marked accordingly.

Marking: Company name or tradename "E180908" or trademark **CYGC · KTG · CYE** ,



, catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2020-11-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

YDPU8.E180908 - Tubing, Extruded Insulating Certified for Canada - Component

Tubing, Extruded Insulating Certified for Canada - Component

See General Information for Tubing, Extruded Insulating Certified for Canada - Component

CHANGYUAN ELECTRONICS GROUP CO LTD
 WOER MANSION 101 ZHUKENG COMMUNITY
 LONGTIAN STREET
 PINGSHAN DISTRICT
 SHENZHEN, GUANGDONG 518118 CHINA

E180908

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable radiation cross-linked Polyolefin tubing					
CB-1000	600	125	All except clear	-	Yes
Not-heat-shrinkable PVC tubing					
CB-300	300	105	BK or CL	-	Yes
CB-600	600	105	BK or CL	-	Yes
Flexible heat shrinkable Polyolefin tubing with liner					
CB-DWT, CB-DWT(XY)	600	125	All except clear	-	Yes
Shrinkable Polyolefin - Flexible					
CB-HFT(TM)	600	125	All except clear	-	No
CB-HFT*, CB-HFT(XY)*, CYG-MT*	300	125	All except clear	-	Yes
CB-HFT, CB-HFT(XY), CYG-MT	600	125	All except clear	-	Yes
Not heat-shrinkable silicone					
CB-SRT	600	150	All except clear	-	Yes (ID size 6.5 to 25 mm only)
Not-heat-shrinkable Polytetrafluoroethylene (PTFE) tubing					
CB-TT-L	150	200	All including clear	-	Yes

CB-TT-S	600	200	All including clear	-	Yes
CB-TT-T	300	200	All including clear	-	Yes
Heat Shrinkable FEP (fluorinated ethylene propylene) Tubing					
CYG-FEP-L	150	200	Clear	-	Yes
CYG-FEP-S	600	200	Clear	-	Yes
CYG-FEP-T	300	200	Clear	-	Yes
Flexible heat-shrinkable modified Fluoropolymer tubing					
CYG-KT	600	150	All including CL	-	Yes
CYG-KYNAR	600	150	CL	-	Yes
Shrinkable Polyolefin - Flexible					
CYG-ZHP	600	125	All except clear	-	Yes
CYG-ZHP *	300	125	All except clear	-	Yes

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

* - Designation is same for 300V and 600V. Tubing shall be marked accordingly.

Marking: Company name or tradename "E180908" or trademark **CYGC, KTG, CYE**

CYG, catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius, date of manufacture (or traceable code) and the Recognized Component Mark for Canada, **UL** printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2020-11-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"