

YDPU2.E203950 - Tubing, Extruded Insulating - Component

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

SHENZHEN WOER HEAT-SHRINKABLE MATERIAL CO LTD

Xinwei Industrial Park, Woer Mansion
Nanshan District, Xili
Shenzhen, Guangdong 518052 CHINA

E203950

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable Polyolefin tubing					
RSFR	600	125	All except clear	-	Yes (Black color only)
RSFR(CB)	300	125	All except clear	-	Yes
RSFR-135G, AMS	600	125	All except clear	-	Yes
RSFR-H	600	125	All except clear	-	Yes
RSFR-HPF	600	125	All except clear	-	Yes
RSFR-HPF(CB)	300	125	All color except clear	-	Yes
Heat shrinkable Polyolefin tubing with meltable liner					
SBRS	600	125	All except clear	-	Yes
Not heat shrinkable PTFE tubing					
WF	600	200	NT	-	Yes
Flexible heat shrinkable Polyolefin tubing					
WKZM-x-yz	600	125	WH	-	No
Not Heat Shrinkable Thin Wall Silicone Rubber Tubing					
WST-300	300	150	white	-	Yes
Not heat shrinkable standard wall Silicone tubing					
WST-600	600	150	WH	-	Yes (ID size 6.5 to 15 mm)

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

x-yz - Where x represents tubing expanded ID, yz represents any alpha and/or numeric combination - for internal client code.

Marking: Company name or tradename "E203950" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2017-09-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

YDPU8.E203950 - Tubing, Extruded Insulating Certified for Canada - Component

Tubing, Extruded Insulating Certified for Canada - Component

See General Information for Tubing, Extruded Insulating Certified for Canada - Component

SHENZHEN WOER HEAT-SHRINKABLE MATERIAL CO LTD

E203950


Xinwei Industrial Park, Woer Mansion
Nanshan District, Xili
Shenzhen, Guangdong 518052 CHINA

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable Polyolefin tubing					
RSFR	600	125	All except clear	-	Yes (Black color only)
RSFR(CB)	300	125	All except clear	-	Yes
RSFR-135G, AMS	600	125	All except clear	-	Yes
RSFR-H	600	125	All except clear	-	Yes
RSFR-HPF	600	125	All except clear	-	Yes
RSFR-HPF(CB)	300	125	All color except clear	-	Yes
Heat shrinkable Polyolefin tubing with meltable liner					
SBRS	600	125	All except clear	-	Yes
Not heat shrinkable PTFE tubing					
WF	600	200	NT	-	Yes
Flexible heat shrinkable Polyolefin tubing					
WKZM-x-yz	600	125	WH	-	No
Not Heat Shrinkable Thin Wall Silicone Rubber Tubing					
WST-300	300	150	white	-	Yes
Not heat shrinkable standard wall Silicone tubing					
WST-600	600	150	WH	-	Yes (ID size 6.5 to 15 mm)

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

x-yz - Where x represents tubing expanded ID, yz represents any alpha and/or numeric combination - for internal client code.

Marking: Company name or tradename "E203950" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius, date of manufacture (or traceable code) and the Recognized Component Mark for Canada,  printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2017-09-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"