



Maximum Leakage Current (L-G) @115VAC/60Hz	Maximum Leakage Current (L-G) @250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm sys.) Freq. - MHz							Min. diferential mode insertion loss (L-L) (dB in 50 ohm sys.) Freq. - MHz							
		.05	.10	.15	.50	1.0	5.0	10	30	.05	.10	.15	.50	1.0	5.0	10
0.25 mA	0.45 mA	15	16	25	30	40	45	40	6	6	30	48	40	40	40	40

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.

DIMENSIONS IN MILLIMETERS

TITLE Module

DRAFT BY: JPC DATE: 5-5-2003

PART NUMBER: 83510031

DRAFTING APPROVAL: DATE:

MATERIAL:

DO NOT SCALE

INTERPOWER CORPORATION

SHEET 1 OF 1

REV	CHANGE DESCRIPTION	DATE	INITIALS
A	Adjusted dimnsions per updated supplier drawing.	9/12/08	DDF