



PANEL CUTOUT

Note 1: Recommended diameter for thru-hole (screw/nut combination) hardware mounting method. Other methods will require holes with different dimensions and parameters.

Filter Specifications																		
Max. Leakage Current (L-G) @ 120VAC/60Hz	Max. Leakage Current (L-G) @ 250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm system) Freq. - MHz								Min. differential mode insertion loss (L-L) (dB in 50 ohm system) Freq. - MHz								
		.03	.10	.15	.50	1.0	3.0	5.0	10	30	.10	.15	.50	1.0	3.0	5.0	10	30
0.19 mA	0.38 mA	-	5	8	13	18	24	18	34	40	3	8	14	14	24	30	30	35

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.

DIMENSIONS IN MILLIMETERS

TITLE EMI Filtered IEC 60320 C20 Inlet Module

DRAFT BY: RLT DATE: 9-29-05

PART NUMBER: 83550010

DRAFTING APPROVAL: RLT DATE: 9-29-05

A	Added Note 1.	3/28/12	DDF
REV	CHANGE DESCRIPTION	DATE	INITIALS

MATERIAL:

DO NOT SCALE

INTERPOWER CORPORATION

SHEET 1 OF 1