



Note 1: Recommended diameter for thru-hole (screw/nut combination) hardware mounting method. Other methods will require holes with different dimensions and parameters.

### Filter Specifications

Max. Leakage Current (L-G) @ 120VAC/60Hz	Max. Leakage Current (L-G) @ 250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm system) Freq. - MHz								Min. differential mode insertion loss (L-L) (dB in 50 ohm system) Freq. - MHz								
		.03	.10	.15	.50	1.0	3.0	5.0	10	30	.10	.15	.50	1.0	3.0	5.0	10	30
0.19 mA	0.38 mA	-	2	4	9	13	23	28	30	40	3	7	13	13	24	30	30	35

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.

#### DIMENSIONS IN MILLIMETERS

TITLE EMI Filtered IEC 60320 Sheet F Outlet Module

DRAFT BY: RLT DATE: 9-29-05

PART NUMBER: 83550030

DRAFTING APPROVAL: RLT DATE: 9-29-05

MATERIAL:

DO NOT SCALE

INTERPOWER CORPORATION

SHEET 1 OF 1

REV	CHANGE DESCRIPTION	DATE	INITIALS
A	Added dimension information to cutout screw holes and Note 1.	4/09/12	DDF