



Note 1: Recommended diameter for thru-hole (screw/nut combination) hardware mounting method. Other methods will require holes with different dimensions and parameters.

### Filter Specifications

Max. Leakage Current (L-G) @ 120VAC/60Hz	Max. Leakage Current (L-G) @ 250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm system) Freq. - MHz	Min. differential mode insertion loss (L-L) (dB in 50 ohm system) Freq. - MHz
0.19 mA	0.38 mA	.03 .10 .15 .50 1.0 3.0 5.0 10 30	.10 .15 .50 1.0 3.0 5.0 10 30
		- 2 4 9 13 23 28 30 40	3 7 13 13 24 30 30 35

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.

#### DIMENSIONS IN MILLIMETERS

TITLE EMI Filtered IEC 60320 Sheet F Outlet Module

DRAFT BY: DDF DATE: 3/5/24

PART NUMBER: 83550031

DRAFTING APPROVAL: DDF DATE: 3/5/24

A	Replacement for 83550030.	3/5/24	DDF
REV	CHANGE DESCRIPTION	DATE	INITIALS

MATERIAL:

DO NOT SCALE  
SHEET 1 OF 1

INTERPOWER CORPORATION