



Note 1: Recommended diameter for thru-hole (screw/nut combination) hardware mounting method. Other methods will require holes with different dimensions and parameters.

Filter Specifications

Max. Leakage Current (L-G) @ 120VAC/60Hz	Max. Leakage Current (L-G) @ 250VAC/50Hz	Min. common mode insertion loss (L-G) (dB in 50 ohm system) Freq. - MHz								Min. differential mode insertion loss (L-L) (dB in 50 ohm system) Freq. - MHz								
		.03	.10	.15	.50	1.0	3.0	5.0	10	30	.10	.15	.50	1.0	3.0	5.0	10	30
0.19 mA	0.38 mA	-	5	8	13	18	24	18	34	40	3	8	14	14	24	30	30	35

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER CORPORATION.

DIMENSIONS IN MILLIMETERS

TITLE EMI Filtered IEC 60320 Sheet J Outlet Module

DRAFT BY: RLT DATE: 9-29-05

PART NUMBER: 83550050

DRAFTING APPROVAL: RLT DATE: 9-29-05

MATERIAL:

DO NOT SCALE
SHEET 1 OF 1

INTERPOWER CORPORATION

REV	CHANGE DESCRIPTION	DATE	INITIALS
A	Added dimension information to cutout screw holes and Note 1.	4/09/12	DDF